



**ICTC Imp. & Exp. Co., Limited**  
**香港洲际贸易有限公司(义乌)**

Tel: 0086 579 85109364  
 Fax: 0086 579 85109364

Email: [nickbriant@yourchinagent.com](mailto:nickbriant@yourchinagent.com)  
[Http://www.yourchinagent.com](http://www.yourchinagent.com)



	Sample	20"GP	40"GP
5. 5HP	USD308	USD295	USD293
6. 5HP	USD310	USD297	USD295

<b>SPECIFICATIONS</b>		<b>snow-001</b>
Max working load		800lbs./minute. (theoretical)
Max. throwing distance		10-15m (theoretical)
Max.working width		20"(56cm)
Max.working thickness		20"(51cm)
Chute rotating angle		190 Degree
<b>Engine type</b>		
Engine type		GX210,7.0 HP
Starting system		Recoil
Fuel tank capacity		3.6 L (0.95 US gallon)
Operational Capacity per tankful (approx.)		4.0 hrs
Type of transmission		Friction disc
Type of wheels		13X5.00-6 inch, Snow hog Tubeless tyres
N.W/G.W		75.0/83.0KG
Packing Dimension		910×640×710CM(mm)
Conveyance		63Pcs/20'GP;132Pcs/40'GP



	Sample	20"GP	40"GP
5. 5HP	USD350	USD338	USD333
6. 5HP	USD360	USD340	USD335

<b>SPECIFICATIONS</b>		<b>snow-002</b>
Max working load		1600lbs./minute. (theoretical)
Max. throwing distance		10-15m (theoretical)
Max.working width		22"(56cm)
Max.working thickness		20"(51cm)
Chute rotating angle		190 Degree
<b>Engine type</b>		
Engine type		GX210,7.0 HP
Starting system		Recoil
Fuel tank capacity		3.6 L (0.95 US gallon)
Operational Capacity per tankful (approx.)		4.0 hrs
Type of transmission		Recoil& Electrical starter
Stage gears		4 Forward, and 2 Reverse
Type of wheels		13X5.00-6 inch, Snow hog pneumatic tyres
N.W/G.W		75.0/83.0KG
Packing Dimension		910×640×710CM(mm)
Conveyance		63Pcs/20'GP;132Pcs/40'GP



	Sample	20"GP	40"GP
5. 5HP	USD360	USD360	USD355
6. 5HP	USD370	USD362	USD357

<b>SPECIFICATIONS</b>		<b>snow-003</b>
Max working load		1600lbs./minute. (theoretical)
Max. throwing distance		10-15m (theoretical)
Max.working width		22"(56cm)
Max.working thickness		91×64×71cm
Chute rotating angle		63Pcs/20'GP;132Pcs/40'GP
<b>Engine type</b>		
Fuel tank capacity		3.6 L (0.95 US gallon)
Operational Capacity per tankful (approx.)		4.0 hrs
Type of transmission		Friction disc
Stage gears		4 Forward, and 2 Reverse
Type of wheels		13X5.00-6 inch, Snow hog pneumatic tyres
N.W/G.W		78.0/88.0KG
Packing Dimension		91×64×71cm
Conveyance		63Pcs/20'GP;132Pcs/40'GP



**ICTC Imp. & Exp. Co., Limited**  
**香港洲际贸易有限公司(义乌)**

Tel: 0086 579 85109364  
 Fax: 0086 579 85109364

Email: [nickbriant@yourchinagent.com](mailto:nickbriant@yourchinagent.com)  
[Http://www.yourchinagent.com](http://www.yourchinagent.com)



				<b>SPECIFICATIONS</b>		<b>snow-004</b>	
				Max working load	2000lbs./minute. (theoretical)		
				Max. throwing distance	10-15m (theoretical)		
				Max.working width	28"(71cm)		
				Max.working thickness	20"(51cm)		
				Chute rotating angle	190 Degree		
				<b>Engine type</b>			
				Engine type	GX270,9.0 HP		
				Starting system	Recoil& Electrical starter		
				Fuel tank capacity	6.0 L (1.59 US gallon)		
				Operational Capacity per tankful (approx.)	3.5 hrs		
				Type of transmission	Friction disc		
				Stage gears	5 Forward, and 2 Reverse		
				Type of wheels	13X5.00-6 inch, Snow hog pneumatic tyres		
	<b>Sample</b>	<b>20"GP</b>	<b>40"GP</b>	N.W/G.W	85.0/95.0KG		
<b>8HP</b>	<b>USD498</b>	<b>USD493</b>	<b>USD488</b>	Packing Dimension	115X76X80 cm		
<b>9HP</b>	<b>USD510</b>	<b>USD495</b>	<b>USD490</b>	Conveyance	30Pcs/20"GP;90Pcs/40"GP		



				<b>SPECIFICATIONS</b>		<b>snow-005</b>	
				Max working load	2000lbs./minute. (theoretical)		
				Max. throwing distance	10-15m (theoretical)		
				Max.working width	28"(71cm)		
				Max.working thickness	22"(55cm)		
				Chute rotating angle	190 Degree		
				<b>Engine type</b>			
				Engine type	GX420,13.0 HP		
				Starting system	Recoil& Electrical starter		
				Fuel tank capacity	6.0 L (1.59 US gallon)		
				Operational Capacity per tankful (approx.)	3.5 hrs		
				Type of transmission	Friction disc		
				Stage gears	5 Forward, and 2 Reverse		
				Type of wheels	13 inch, Snow hog pneumatic tyres		
	<b>Sample</b>	<b>20"GP</b>	<b>40"GP</b>	N.W/G.W	120 kg		
<b>11HP</b>	<b>USD710</b>	<b>USD665</b>	<b>USD660</b>	Packing Dimension	115X76X80 cm		
<b>13HP</b>	<b>USD715</b>	<b>USD672</b>	<b>USD668</b>	Conveyance	30Pcs/20"GP;90Pcs/40"GP		



				<b>SPECIFICATIONS</b>		<b>snow-007</b>	
				Max working load	800lbs./minute. (theoretical)		
				Max. throwing distance	2-8m (theoretical)		
				Max.working width	20"(52cm)		
				Max.working thickness	11"(28cm)		
				Chute rotating angle	190 Degree		
				<b>Engine type</b>			
				Engine type	GX120,4.0 HP		
				Starting system	Recoil		
				Fuel tank capacity	2.5 L (0.66 US gallon)		
				Operational Capacity per tankful (appr)	3.5 hrs		
				Type of transmission	Belt		
				Type of wheels	8 inch, Snow hog Tubeless tyres		
	<b>Sample</b>	<b>20"GP</b>	<b>40"GP</b>	N.W/G.W	38.0/43.0KG		
<b>4HP</b>	<b>USD280</b>	<b>USD225</b>	<b>USD215</b>	Packing Dimension	690×560×470CM(mm)		
				Conveyance	160Pcs/20"GP;320Pcs/40"GP		



**ICTC Imp. & Exp. Co., Limited**  
**香港洲际贸易有限公司(义乌)**

Tel: 0086 579 85109364  
 Fax: 0086 579 85109364

Email: [nickbriant@yourchinagent.com](mailto:nickbriant@yourchinagent.com)  
[Http://www.yourchinagent.com](http://www.yourchinagent.com)



<b>SPECIFICATIONS</b>		<b>snow-008</b>	
Max working load	2000lbs./minute. (theoretical)		
Max. throwing distance	10-15m (theoretical)		
Max.working width	28"(71cm)		
Max.working thickness	22"(55cm)		
Chute rotating angle	190 Degree		
<b>Engine type</b>			
Engine type	GX420,13.0 HP		
Starting system	Recoil& Electrical starter		
Fuel tank capacity	6.0 L (1.59 US gallon)		
Operational Capacity per tankful (approx.)	3.5 hrs		
Type of transmission	Friction disc		
Stage gears	5 Forward, and 2 Reverse		
Type of wheels	13 inch, Snow hog pneumatic tyres		
N.W/G.W	120 kg		
Packing Dimension	115X76X80 cm		
Conveyance	30Pcs/20"GP;90Pcs/40"HQ		

	Sample	20"GP	40"GP
11HP	USD705	USD691	USD686
13HP	USD720	USD695	USD690



<b>SPECIFICATIONS</b>		<b>snow-009</b>	
Max working load	1600lbs./minute. (theoretical)		
Max. throwing distance	10-15m (theoretical)		
Max.working width	22"(56cm)		
Max.working thickness	91×64×71cm		
Chute rotating angle	63Pcs/20"GP;132Pcs/40"GP		
<b>Engine type</b>			
Engine type	GX210,7.0 HP		
Starting system	Recoil& Electrical starter		
Fuel tank capacity	3.6 L (0.95 US gallon)		
Operational Capacity per tankful (approx.)	4.0 hrs		
Type of transmission	Recoil& Electrical starter		
Stage gears	4 Forward, and 2 Reverse		
Type of wheels	13X5.00-6 inch, Snow hog pneumatic tyres		
N.W/G.W	78.0/88.0KG		
Packing Dimension	91×64×71cm		
Conveyance	63Pcs/20"GP;132Pcs/40"GP		

	Sample	20"GP	40"GP
5. 5HP	USD385	USD375	USD370
6. 5HP	USD390	USD377	USD372



<b>SPECIFICATIONS</b>		<b>snow-010</b>	
Max working load	2000lbs./minute. (theoretical)		
Max. throwing distance	10-15m (theoretical)		
Max.working width	28"(71cm)		
Max.working thickness	20"(51cm)		
Chute rotating angle	190 Degree		
<b>Engine type</b>			
Engine type	GX270,9.0 HP		
Starting system	Recoil& Electrical starter		
Fuel tank capacity	6.0 L (1.59 US gallon)		
Operational Capacity per tankful (approx.)	3.5 hrs		
Type of transmission	Friction disc		
Stage gears	5 Forward, and 2 Reverse		
Type of wheels	13X5.00-6 inch, Snow hog pneumatic tyres		
N.W/G.W	85.0/95.0KG		
Packing Dimension	115X76X80 cm		
Conveyance	30Pcs/20"GP;90Pcs/40"HQ		

	Sample	20"GP	40"GP
8HP	USD560	USD533	USD528
9HP	USD570	USD535	USD530



**ICTC Imp. & Exp. Co., Limited**  
**香港洲际贸易有限公司(义乌)**

Tel: 0086 579 85109364  
 Fax: 0086 579 85109364

Email: [nickbriant@yourchinagent.com](mailto:nickbriant@yourchinagent.com)  
[Http://www.yourchinagent.com](http://www.yourchinagent.com)



<b>SPECIFICATIONS</b>		<b>snow-011</b>	
Max working load	800lbs./minute. (theoretical)		
Max. throwing distance	10-15m (theoretical)		
Max.working width	20"(56cm)		
Max.working thickness	20"(51cm)		
Chute rotating angle	190 Degree		
<b>Engine type</b>			
Engine type	GX210,7.0 HP		
Starting system	Recoil		
Fuel tank capacity	3.6 L (0.95 US gallon)		
Operational Capacity per tankful (approx.)	4.0 hrs		
Type of transmission	Recoil& Electrical starter		
Type of wheels	13X5.00-6 inch, Snow hog Tubeless tyres		
	N.W/G.W		
	75.0/83.0KG		
	Packing Dimension		
	910×640×710CM(mm)		
	Conveyance		
	63Pcs/20'GP;132Pcs/40'GP		

	<b>Sample</b>	<b>20"GP</b>	<b>40"GP</b>
<b>5. 5HP</b>	<b>USD348</b>	<b>USD338</b>	<b>USD334</b>
<b>6. 5HP</b>	<b>USD350</b>	<b>USD340</b>	<b>USD336</b>